



Mobil™ Brake Fluid DOT 5.1

Product Description

High performance brake fluid for use in modern, high performance vehicles. Minimum wet boiling point of 180°C.

Mobil Brake Fluid DOT 5.1 is based on polyethylene glycol ether technology to provide the highest level of brake and clutch performance in modern as well as older model automotive and commercial vehicles.

Directions for use:

1. 1. Follow vehicle manufacturer’s recommendations. 2. Keep Brake Fluid clean and dry. 3. Store in original container only. 4. Keep container clean and tightly closed to prevent water absorption. 5. Do not refill container and do not use for other liquids. 6. Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf life:

- 3 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

Typical Inspections Data:	
Colour	Straw
Density @ 20°C	1.068 g/cm3
Equilibrium Reflux Boiling Point	278 °C
Wet Equilibrium Reflux Boiling Point	183 °C
pH (50% EtOH)	7.3
Viscosity CCS @ - 40°C	850 cst